

The **Fast Feed 520** utilizes a precision feed system suitable for almost any type of screw. The Fast Feed 520 also features three adjustments giving the user superb control over feed speed and time. Thanks to the superior design of the rail, it can be easily adjusted to feed screw sizes from 1.0 to 5.2 mm.



Model: DRFF520

Specifications:

- Screw Diameter: #0 - #10 (1.0 - 5.2 mm)
- Screw Length: 0.75 in (19 mm) max
- Weight: 5.4 lbs (2.45 kg)
- Dimensions: 4.9x7.2x5.6 in (125x183x142 mm)

*Accepts most types of screws including screws with captive washers.

- Adjustable from 1.0-5.2mm (#0-#10)
- Quiet operation, easy to service
- Includes AC adapter and rail adjustment kit
- Single rail accomodates entire range of screw sizes
- Less moving parts increases durability and lowers maintenance
- Accepts most types of screws, including screws with captive washers
- Vibration Time, Vibration Intensity, and Drum Rotation Time adjustments allow the user to optimize the screw feed rate



Rail Adjustment Kit

Each Fast Feed 520 includes:

- AC adapter (100-240VAC/15VDC)
- Rail adjustment kit

FAST FEEDING SPEED

Because the hopper supplies a large quantity of screws to the rail and the rail feeds the screws smoothly, the screw feeding speed is faster than other similar feeders.

FEATURES

The Fast Feed 520 is compact and lightweight. It costs only a fraction of the price of a conventional bowl feeder. Features multiple adjustments including: Vibration Timer, Vibration Intensity, and Drum Timer. These adjustments allow you to fine tune the unit to your specific application and screw type.